



AT PE5216G-AX-G

Vaše cena s DPH: **12.838 CZK**

Skladem: **NE**

Výrobce: Aten International Co., Ltd.

Záruka: 24 měsíců



ATEN PE5216G-AX-G

napájecí jednotka (PDU)

20A/16A 16-Outlet Metered eco PDU

vstup: IEC 60320 C20

výstup: 14 x IEC320 C13 + 2 x IEC320 C19

As part of its NRGence line, ATEN has developed a new generation of green energy power distribution units (PDUs) to effectively increase the efficiency of data center power usage. The NRGence PE5216 eco PDU is an intelligent PDU that contains 16 AC outlets and is available in various IEC or NEMA socket configurations. It provides the ability to monitor the center's health environment via sensors*. NRGence eco PDU offers real-time power measurement – allowing you to monitor the power status of devices attached to the PDUs, either at the PDU device or Bank level, from practically any location via a TCP/IP connection. It also offers comprehensive power analysis reports – providing precise measurements of current, voltage, power and watt-hour in a real-time Display. NRGence eco PDU supports any 3rd party v1, v2 & v3 SNMP Manager Software and ATEN eco Sensors (eco PDU Manager Software). eco Sensors provides you with an easy method for managing multiple devices, offering an intuitive and user-friendly Graphical User Interface that allows you to configure a PDU device and monitor power status of the equipment connected to it. With its advanced security features and ease of operation, the eco PDU is the most convenient, most reliable, and most cost effective way to remotely monitor power status for multiple computer installations and allocate power resources in the most efficient way possible. * Sensors are optional accessories. A sensor-enabled installation is required to generate a more complete energy-efficient data and chart.